

LIGHT COMMERCIAL CLAD OUTSWING DOOR
- FULL VIEW DOOR/SIDELITE



LIGHT COMMERCIAL OUTSWING DOOR													
Unit Type	Callout	Frame Size		Rough Opening		Masonry Opening		Glass Size		Daylight Opening		Sash Size	
		Ft-in	mm	Ft-in	mm	Ft-in	mm	Ft-in	mm	Ft-in	mm	Ft-in	mm
Light Commercial Door WIDTH	2/6	2'-7 ⁵ / ₈ "	(803)	2'-8 ⁵ / ₈ "	(829)	2'-8 ¹ / ₈ "	(841)	1'-8 ¹ / ₈ "	(511)	1'-7"	(511)	2'-5 ¹³ / ₁₆ "	(757)
	3/0	3'-1 ⁵ / ₈ "	(956)	3'-2 ⁵ / ₈ "	(981)	3'-2 ¹ / ₈ "	(994)	2'-2 ¹ / ₈ "	(664)	2'-1"	(664)	2'-11 ¹³ / ₁₆ "	(910)
	3/6	3'-7 ⁵ / ₈ "	(1108)	3'-8 ⁵ / ₈ "	(1133)	3'-8 ¹ / ₈ "	(1146)	2'-8 ¹ / ₈ "	(816)	2'-7"	(816)	3'-5 ¹³ / ₁₆ "	(1062)
	5/0	5'-1 ¹¹ / ₁₆ "	(1567)	5'-2 ¹¹ / ₁₆ "	(1592)	5'-2 ³ / ₁₆ "	(1580)	1'-8 ¹ / ₈ "	(511)	1'-7"	(511)	2'-5 ¹³ / ₁₆ "	(757)
	6/0	6'-1 ¹¹ / ₁₆ "	(1872)	6'-2 ¹¹ / ₁₆ "	(1897)	6'-2 ³ / ₁₆ "	(1884)	2'-2 ¹ / ₈ "	(664)	2'-1"	(664)	2'-11 ¹³ / ₁₆ "	(910)
	7/0	7'-1 ¹¹ / ₁₆ "	(2176)	7'-2 ¹¹ / ₁₆ "	(2202)	7'-2 ³ / ₁₆ "	(2189)	2'-8 ¹ / ₈ "	(816)	2'-7"	(816)	3'-5 ¹³ / ₁₆ "	(1062)

LIGHT COMMERCIAL OUTSWING DOOR AND SIDELITE													
Unit Type	Callout	Frame Size		Rough Opening		Masonry Opening		Glass Size		Daylight Opening		Sash Size	
		Ft-in	mm	Ft-in	mm	Ft-in	mm	Ft-in	mm	Ft-in	mm	Ft-in	mm
Light Commercial Door HEIGHT	6/8	6'-8 ⁹ / ₁₆ "	(2046)	6'-9 ¹ / ₁₆ "	(2008)	6'-8 ¹³ / ₁₆ "	(2053)	5'-0 ³ / ₈ "	(1534)	4'-11 ¹ / ₄ "	(1505)	6'-6 ³ / ₄ "	(2000)
	7/0	7'-0 ⁹ / ₁₆ "	(2148)	7'-1 ¹ / ₁₆ "	(2008)	7'-0 ¹³ / ₁₆ "	(2154)	5'-4 ³ / ₈ "	(1635)	5'-3 ¹ / ₄ "	(1607)	6'-10 ³ / ₄ "	(2102)
	8/0	8'-0"	(2438)	8'-0 ¹ / ₂ "	(2046)	8'-0 ¹ / ₄ "	(2445)	6'-3 ¹³ / ₁₆ "	(1926)	6'-2 ¹¹ / ₁₆ "	(1897)	7'-10 ³ / ₄ "	(2392)

LIGHT COMMERCIAL OUTSWING DOOR SIDELITE													
Unit Type	Callout	Frame Size		Rough Opening		Masonry Opening		Glass Size		Daylight Opening		Sash Size	
		Ft-in	mm	Ft-in	mm	Ft-in	mm	Ft-in	mm	Ft-in	mm	Ft-in	mm
Light Commercial Door WIDTH	1/0	1'-1 ⁵ / ₈ "	(346)	1'-2 ⁵ / ₈ "	(371)	1'-2 ¹ / ₈ "	(359)	0'-8 ⁵ / ₈ "	(219)	0'-7 ¹ / ₂ "	(191)	0'-11 ¹³ / ₁₆ "	(300)
	1/4	1'-5 ⁵ / ₈ "	(448)	1'-6 ⁵ / ₈ "	(473)	1'-6 ¹ / ₈ "	(460)	1'-0 ⁵ / ₈ "	(321)	0'-11 ¹ / ₂ "	(292)	1'-3 ¹³ / ₁₆ "	(402)
	1/6	1'-7 ⁵ / ₈ "	(498)	1'-8 ⁵ / ₈ "	(524)	1'-8 ¹ / ₈ "	(511)	1'-2 ⁵ / ₈ "	(371)	1'-1 ¹ / ₂ "	(343)	1'-5 ¹³ / ₁₆ "	(452)
	1/8	1'-9 ⁵ / ₈ "	(549)	1'-10 ⁵ / ₈ "	(575)	1'-10 ¹ / ₈ "	(562)	1'-4 ⁵ / ₈ "	(422)	1'-3 ¹ / ₂ "	(394)	1'-7 ¹³ / ₁₆ "	(503)

OPERATION IS VIEWED FROM EXTERIOR. HINGE SIDE MUST BE SPECIFIED WHEN ORDERING A SINGLE WIDE DOOR.
 SIZES GIVEN ARE FOR UNITS WITH RIM DEVICE TYPE HARDWARE. SUBTRACT ³/₁₆" FROM WIDTH OF A DOUBLE DOOR UNIT WITH MULTI-POINT HARDWARE.
 ADDITIONAL SIZES ARE AVAILABLE UPON REQUEST (2068 TO 3680, 4068 TO 7080).

LIGHT COMMERCIAL CLAD OUTSWING DOOR - TRANSOM



LIGHT COMMERCIAL OUTSWING DOOR SASH SET TRANSOM (NARROW STILE)

Unit Type	Callout	Frame Size		Rough Opening		Masonry Opening		Glass Size		Daylight Opening		Sash Size	
		Ft-in	mm	Ft-in	mm	Ft-in	mm	Ft-in	mm	Ft-in	mm	Ft-in	mm
Light Commercial Door Transom WIDTH	1/0	1'-1 ⁵ / ₈ "	(346)	1'-2 ⁵ / ₈ "	(371)	1'-2 ¹ / ₈ "	(359)	0'-8 ³ / ₄ "	(222)	0'-7 ⁵ / ₈ "	(194)	0'-11 ⁵ / ₈ "	(295)
	1/4	1'-5 ⁵ / ₈ "	(448)	1'-6 ⁵ / ₈ "	(473)	1'-6 ¹ / ₈ "	(460)	1'-0 ³ / ₄ "	(324)	0'-11 ⁵ / ₈ "	(295)	1'-3 ⁵ / ₈ "	(396)
	1/6	1'-7 ⁵ / ₈ "	(498)	1'-8 ⁵ / ₈ "	(524)	1'-8 ¹ / ₈ "	(511)	1'-2 ³ / ₄ "	(375)	1'-1 ⁵ / ₈ "	(346)	1'-5 ⁵ / ₈ "	(448)
	1/8	1'-9 ⁵ / ₈ "	(549)	1'-10 ⁵ / ₈ "	(575)	1'-10 ¹ / ₈ "	(562)	1'-4 ³ / ₄ "	(425)	1'-3 ⁵ / ₈ "	(397)	1'-7 ⁵ / ₈ "	(498)
	2/6	2'-7 ⁵ / ₈ "	(803)	2'-8 ⁵ / ₈ "	(829)	2'-8 ¹ / ₈ "	(841)	2'-2 ³ / ₄ "	(679)	2'-1 ⁵ / ₈ "	(651)	2'-5 ⁵ / ₈ "	(752)
	3/0	3'-1 ⁵ / ₈ "	(956)	3'-2 ⁵ / ₈ "	(981)	3'-2 ¹ / ₈ "	(994)	2'-8 ³ / ₄ "	(832)	2'-7 ⁵ / ₈ "	(803)	2'-11 ⁵ / ₈ "	(905)
	3/6	3'-7 ⁵ / ₈ "	(1108)	3'-8 ⁵ / ₈ "	(1133)	3'-8 ¹ / ₈ "	(1146)	3'-2 ³ / ₄ "	(984)	3'-1 ⁵ / ₈ "	(956)	3'-5 ⁵ / ₈ "	(1057)
	5/0	5'-1 ¹¹ / ₁₆ "	(1567)	5'-2 ¹¹ / ₁₆ "	(1592)	5'-2 ³ / ₁₆ "	(1580)	2'-2 ³ / ₄ "	(679)	2'-1 ⁵ / ₈ "	(651)	2'-5 ⁵ / ₈ "	(752)
	6/0	6'-1 ¹¹ / ₁₆ "	(1872)	6'-2 ¹¹ / ₁₆ "	(1897)	6'-2 ³ / ₁₆ "	(1884)	2'-8 ³ / ₄ "	(832)	2'-7 ⁵ / ₈ "	(803)	2'-11 ⁵ / ₈ "	(905)
	7/0	7'-1 ¹¹ / ₁₆ "	(2176)	7'-2 ¹¹ / ₁₆ "	(2202)	7'-2 ³ / ₁₆ "	(2189)	3'-2 ³ / ₄ "	(984)	3'-1 ⁵ / ₈ "	(956)	3'-5 ⁵ / ₈ "	(1057)

LIGHT COMMERCIAL OUTSWING DOOR SASH SET TRANSOM (WIDE STILE)

Unit Type	Callout	Frame Size		Rough Opening		Masonry Opening		Glass Size		Daylight Opening		Sash Size	
		Ft-in	mm	Ft-in	mm	Ft-in	mm	Ft-in	mm	Ft-in	mm	Ft-in	mm
Light Commercial Door Transom WIDTH	2/6	2'-7 ⁵ / ₈ "	(803)	2'-8 ⁵ / ₈ "	(829)	2'-8 ¹ / ₈ "	(841)	1'-8 ¹ / ₄ "	(514)	1'-7 ¹ / ₈ "	(486)	2'-5 ⁵ / ₈ "	(752)
	3/0	3'-1 ⁵ / ₈ "	(956)	3'-2 ⁵ / ₈ "	(981)	3'-2 ¹ / ₈ "	(994)	2'-2 ¹ / ₄ "	(667)	2'-1 ¹ / ₈ "	(638)	2'-11 ⁵ / ₈ "	(905)
	3/6	3'-7 ⁵ / ₈ "	(1108)	3'-8 ⁵ / ₈ "	(1133)	3'-8 ¹ / ₈ "	(1146)	2'-8 ¹ / ₄ "	(819)	2'-7 ¹ / ₈ "	(791)	3'-5 ⁵ / ₈ "	(1057)
	5/0	5'-1 ¹¹ / ₁₆ "	(1567)	5'-2 ¹¹ / ₁₆ "	(1592)	5'-2 ³ / ₁₆ "	(1580)	1'-8 ¹ / ₄ "	(514)	1'-7 ¹ / ₈ "	(486)	2'-5 ⁵ / ₈ "	(752)
	6/0	6'-1 ¹¹ / ₁₆ "	(1872)	6'-2 ¹¹ / ₁₆ "	(1897)	6'-2 ³ / ₁₆ "	(1884)	2'-2 ¹ / ₄ "	(667)	2'-1 ¹ / ₈ "	(638)	2'-11 ⁵ / ₈ "	(905)
	7/0	7'-1 ¹¹ / ₁₆ "	(2176)	7'-2 ¹¹ / ₁₆ "	(2202)	7'-2 ³ / ₁₆ "	(2189)	2'-8 ¹ / ₄ "	(819)	2'-7 ¹ / ₈ "	(791)	3'-5 ⁵ / ₈ "	(1057)

LIGHT COMMERCIAL OUTSWING DOOR & SIDELITE SASH SET TRANSOM

Unit Type	Callout	Frame Size		Rough Opening		Masonry Opening		Glass Size		Daylight Opening		Sash Size	
		Ft-in	mm	Ft-in	mm	Ft-in	mm	Ft-in	mm	Ft-in	mm	Ft-in	mm
Light Commercial Door Transom HEIGHT	1/0	1'-0"	(305)	1'-0 ¹ / ₂ "	(318)	1'-0 ¹ / ₄ "	(311)	0'-7 ¹ / ₈ "	(181)	0'-6"	(152)	0'-10"	(254)
	1/2	1'-2"	(356)	1'-2 ¹ / ₂ "	(368)	1'-2 ¹ / ₄ "	(362)	0'-9 ¹ / ₈ "	(232)	0'-8"	(203)	1'-0"	(305)
	1/6	1'-6"	(457)	1'-6 ¹ / ₂ "	(470)	1'-6 ¹ / ₄ "	(464)	1'-1 ¹ / ₈ "	(333)	1'-0"	(305)	1'-4"	(406)
	1/8	1'-8"	(508)	1'-8 ¹ / ₂ "	(521)	1'-8 ¹ / ₄ "	(514)	1'-3 ¹ / ₈ "	(384)	1'-2"	(356)	1'-6"	(457)

SIZES GIVEN ARE FOR UNITS MULLED ABOVE DOORS WITH RIM DEVICE TYPE HARDWARE. SUBTRACT ³/₁₆" FROM WIDTH, IF MULLED ABOVE DOUBLE DOOR WITH MULTI-POINT HARDWARE. ADDITIONAL SIZES ARE AVAILABLE UPON REQUEST.